


PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification⁶ : B60P 7/06, B60R 13/08</p>	<p>A1</p>	<p>(11) International Publication Number: WO 00/02747 (43) International Publication Date: 20 January 2000 (20.01.00)</p>
<p>(21) International Application Number: PCT/US98/14333 (22) International Filing Date: 10 July 1998 (10.07.98) (71) Applicant (for all designated States except US): EFTEC NORTH AMERICA L.L.C. [US/US]; 31601 Research Park Drive, Madison Heights, MI 48071 (US). (72) Inventor; and (75) Inventor/Applicant (for US only): PEREYRA, Sergio, O. [BR/BR]; Rua Professor Joaquim Silva, 669, Caixa Postal 777, CEP-18085-000 Sorocaba, SP (BR). (74) Agents: QUAN, Nancy, N. et al.; 1200 Willow Lake Boulevard, St. Paul, MN 55110-5101 (US).</p>		<p>(81) Designated States: BR, CA, CN, JP, KR, MX, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report.</p>
<p>(54) Title: METHOD FOR BLOCKING PASSAGES AND THE CAVITY FILLING BAG</p> <p>(57) Abstract</p> <p>A bag (10) is formed of a flexible material which may be inserted into a cavity (31) of a vehicle (20) and inflated to block the flow of powder, gas and/or fluids and to restrict vibration and dampen noise.</p> 		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

METHOD FOR BLOCKING PASSAGES AND THE CAVITY FILLING BAG

Field of the Invention

This invention relates to a bag or bladder for filling cavities for deadening
5 vibrations, stiffening body panels, blocking a passage and an improved method thereof.
In one aspect, the present invention is related to a gas filled bag adapted to fit in an open
space or cavity in vehicles, recreational vehicles, boats and other related devices to block
passages (against the passage of air, dust and fluids), provide buoyancy, dampen
vibrations, and stiffen body panels adjacent to the bladder which improves NVH (noise,
10 vibration and harshness) values and reduces the tendency of the panels to deform under
an applied pressure.

Description of the Prior Art

The prior art is replete with teachings of inflatable bags, for example dunnage
15 bags, used in shipping to fill or bridge the space left between the freight and the walls of
the freight carrying compartment, see U.S. Patents Re. 27,787, 3,199,689, 3,426,891,
3,667,625 and 4,553,887. U.S. Patent 2,907,580 also illustrates the use of an inflatable
bag for holding down the load in the trunk of an automobile. This patent also discusses
the fact the bag should be fairly thin so that it may flex sharply without cracking, that it
20 should be mechanically very strong, substantially air tight and abrasion resistant.
Examples of materials are given.

In the field of the present invention, foams or preformed panels of plastic or
rubber-like materials are used in the construction of vehicles and boats to provide
barriers, sound and vibration dampening and buoyancy. Construction by robotics
25 techniques have resulted in designs to reduce the amount of labor involved and have
increased the size of the units joined in the manufacture of such devices. Further, the
techniques for automatically welding the units together have generated cavities which
need filling to provide a barrier for powder, gas and fluid in such cavities or passageways
left after the automated construction.

30 Other known forms of filling cavities include the use of foaming materials, which
are blown or formed in situ.

The present invention differs from the prior art in that the invention described is not a dunnage bag to hold pieces in place in the automobile or similar vehicle, or a formed integral part of the vehicle. The device and method of the present invention can be sold in the original equipment for the purpose described or in the after market to provide particularly useful accessories for some vehicles if the buyer desires.

Summary of the Invention

The present invention provides a bag or bladder and a new and improved process thereof for reducing sound transmission, vibration propagation, and general disagreeable noises, i.e., harshness (collectively termed NVH), resulting from spaces existing between panels or compartments on vehicles, stiffening adjacent body panels adjacent to the bladder which improves NVH (noise, vibration and harshness) values and reduces the tendency of the panels to deform under an applied pressure, and to block passages existing in vehicles to restrict the passage of powder, gas and/or fluids from moving through the passageway.

Harshness as used herein is a term used to describe a disagreeable noise resulting from the vehicle reacting to its environment.

Panel stiffening describes a process in which a sub-assembly of a vehicle such as a fender or door, etc., becomes more structurally sound via a more rigid alignment or joining of the parts that comprise it. The more rigid a vehicle becomes, the better the drivability becomes, and the quieter it becomes. Panel stiffening also refers to the decrease in the tendency of a panel to deform under an applied pressure when such deformable panels are not reinforced by other means.

The present invention provides a process for blocking a passageway, stiffening adjacent body panels, restricting noise, vibration and harshness, and comprises the steps of: forming an inflatable bag having a valve to permit inflation and sealing of the bag, folding the bag to a desired configuration; inserting the folded bag into a cavity where powder, gas or fluids may pass and/or which may cause noise and vibrations; inflating the bag with a gas under pressure to form the bag to the interior of said cavity; and sealing the bag.

The bag for use in the process comprises at least a pair of similar panels joined and sealed at their edges, one of said panels having a valve positioned adjacent to an edge to permit inflation of the bag and sealing of the inflated bag. The bag is formed of a gas impermeable flexible material. When inflated, the bag will follow the contour of the inside of the cavity it fills.

The bags can be a variety of shapes, though more commonly oblong or diamond shape. The sizes of the bag can also vary, from as small as 1 inch (2.5 cm.) across to as large across as the size of a body side panel.

10 **Brief Description of the Drawings**

The present invention will be further described with reference to the accompanying drawings wherein:

Figure 1 is a side elevational view of an inflatable cavity bag according to the present invention;

15 Figure 2 is an elevational view of a cavity bag rolled for insertion into a cavity through a preformed opening;

Figure 3 is a schematic view of the cavity bag being inflated from a cylinder of gas;

Figure 4 is a schematic view of a vehicle body having a passageway existing between the exterior panel and the bed wherein a cavity is formed;

Figure 5 is a cross-sectional view of the exterior panel and bed of the vehicle at the wheel-well showing the cavity that exists;

Figure 6 is a schematic view of the vehicle body with the cavity bag in place in the cavity to block powder, gas or fluid from passing through the passage to the cab of the vehicle; and

25 Figure 7 is a detail view of the vehicle bed assembly with a preformed cavity bag in position to close the cavity after the fender panel is welded to the bed assembly.

Detailed Description and Description of the Preferred Embodiment

30 The present invention provides an improved method for sound deadening, vibration dampening, harshness reduction, and stiffening of adjacent body panels for

vehicles, i.e., automobiles, trucks, boats or airplanes, and for blocking passages in vehicles to seal the passageways against the passage of powder, gas or fluid through the passageway. Further, the present invention provides an inflatable cavity bag for blocking a passageway to restrict the egress of powder, gas or fluids through the passageway. The cavity bag of the present invention is adapted to be installed during the manufacture or as an after-market product and comprises a bag formed with at least two panels sealed together about their adjoining edges to define an inflatable bag with a valve sealed to one of the panels adjacent to an edge thereof to permit inflation of the bag and sealing the inflation gas within the bag. The cavity may be in a rocker panel, a removable access panel, column, door, roof, an opening behind a sub-assembly such as a tail lamp, a stoppered drain hole and other stoppered holes or other area as described herein.

Referring to Figure 1 of the drawing, there is illustrated a cavity bag **10** formed of a pair of panels **11**, only one of which is visible, having a generally oblong or diamond shape, with a valve **12** sealed on one panel **11**, adjacent to an edge to permit gas to be introduced into the bag and sealed therein. The bag **10** can be fabricated from polymers that are substantially impermeable to any filling gases such as nitrogen, carbon dioxide, argon and others. The polymers can include polyvinylchloride (PVC), styrene butadiene rubber (SBR), neoprene, polyesters including polyethylene terephthalate (PET) such as mylar, polyethylene, nylon and other flexible gas impermeable material which can be sealed together. Natural rubber materials and compounds may also be used. Preferably, the bag is formed of a material which is substantially gas impermeable. The panels for the bags can either be extruded, molded, cast or any other suitable methods. For the polymers that are less impermeable to gases, a thicker panel can be used, or they can be metallized to improve the impermeability, the same techniques as those employed in metallized balloons. Thus, some polymeric materials having metal coatings would also be suitable bag materials. Multiple polymeric layers can also be laminated or coextruded to form a panel to improve the gas impermeability.

The bag can be constructed with removable caps so that if gas is leaked out over years, it can be refilled. Of course, used bags themselves can also be replaced with new ones if they become ineffective or worn.

The outer surface of the panel can be treated to increase the coefficient of friction so that it can stay in place when inflated against the metal or plastic part of the vehicle. The treatment can include application of a pressure sensitive adhesive, either permanent or removable.

5 The shape and volume of the bag 10 may vary depending on the various needs for the bag. One example, as illustrated in Figure 1, is a bag 40 cm long by 17 cm wide with the center of a valve 12 positioned 5 cm from one end.

Figure 2 shows the bag 10 in a folded position with the edges folded or rolled inward to define a cylindrical shape with the valve 12 exposed at one end to provide
10 access such that the bag 10 can be inserted into a cavity through an opening and then the bag can be inflated to peel the tape strips 15, holding the bag in rolled form, to expand the bag 10 into the cavity. The tape strips 15 are short lengths of a pressure sensitive tape which will peel from the surface of the folded bag upon inflation.

As shown in Figure 3, the bag 10 is preferably inflated by a gas, such as nitrogen,
15 from a tank 16 at a preset pressure as indicated by the pressure gauge 18 in the line 19. The gas is inserted into the bag 10 through the valve 12 by a suitable gun or cooperating valve mating with the valve 12 on the cavity bag 10.

The vehicle is formed with numerous cavities in the manufacture and, depending on their location, create cavities where the panels of the vehicle can even vibrate causing
20 noises to be present in the vehicle. An example is illustrated in Figures 4, 5 and 7, where the vehicle 20 is formed with a panel 22 forming at least a portion of the bed, generally designated 24, of a pickup type truck including a fender well 26 in the bed and forming the wall 28 over the wheel (not shown). When the decorative outer panel 30 is placed over the outer side of the panel 22 and welded thereto, a cavity 31 is formed as shown in
25 Figure 5. This cavity 31 extends actually from the tail-light assembly 32 to the interior of the cab 33.

As indicated in Figure 5, an opening can be formed in the panel 22 with a rubber grommet or stopper 34 in the hole. To install the cavity bag 10, the stopper is removed and the cavity bag 10 is inserted through the hole into the cavity with the valve 12
30 positioned at the hole. The cavity bag is then inflated to fill the cavity at the position of

the hole in the cavity 31. The valve 12 is then closed and the stopper replaced in the hole.

On the original equipment, a cavity sealing bag 40 may be attached to the outer side of the panel 22 as shown in Figure 7. The bag 40 is folded and deflated to allow the
5 outer decorative panel to be placed over the panel 22 and bag 40. After assembly, the bag 40 can be inflated through a valve (not shown), disposed at an opening in the panel 22 and accessible through the bed to inflate the bag 40. As also shown in Figure 7, the wire harness 41 for the tail-light assembly 32 extends through the cavity 31 prior to the assembly of the outer panel onto the vehicle.

10 As mentioned before, such bags not only reduce sound transmission, vibration propagation, and other general disagreeable noises, i.e., harshness (collectively termed NVH), resulting from spaces existing between panels or compartments on vehicles, but also block passages existing in vehicles to restrict the passage of powder, gas and/or fluids from moving through the passageway. Surprisingly, they also stiffen adjacent
15 body panels adjacent to the bladder, thus improving NVH (noise, vibration and harshness) values and reducing the tendency of the panels to deform under an applied pressure. This eliminates the need for reinforcing certain panels, increases the use of plastics, and gives manufacturers the option to use thinner gauge materials, either metal or plastic, in the fabrication of vehicles, as described above. This can reduce the weight
20 of the vehicles and further improves their fuel efficiency.

Having described the present invention with reference to the several views of the drawing, what the applicant regards as the invention, including variations thereof as may come within the scope of the invention, is set forth in the appended claims.

Claims

1. A process for blocking a passageway, stiffening adjacent body panels and restricting noise, vibration and harshness comprising the steps of:
 - a) providing an inflatable bag (10, 40) having a valve (12) to permit inflation and sealing of the bag;
 - b) inserting said bag into a cavity (31) where powder, gas or fluids may pass and/or which may cause noise and vibration;
 - d) inflating said bag with a gas under pressure to form said bag to the interior of said cavity; and
 - e) sealing said bag.
2. The process of Claim 1 wherein said bag is folded to a desired configuration prior to insertion into a cavity.
3. The process of Claim 1 wherein said bag is treated to provide an increase coefficient of friction.
4. The process of Claim 1 wherein said cavity is found in a vehicle.
5. The process of Claim 1 wherein said cavity is found in a location in a vehicle selected from a group consisting of a rocker panel, a removable access panel, a column, a door, a roof, an opening behind a sub-assembly rocker panel, a stoppered drain hole and other stoppered holes.
6. The process of Claim 1 wherein said bag is adapted to be re-inflated and resealed.
7. The process of Claim 1 wherein said bag is formed of at least two panels, the panel of said bag is made by a method selected from the group consisting of casting, molding, extruding, coextruding, lamination and combinations thereof.

8. The process of Claim 1 wherein said bag is formed of at least two panels, said panels of said bags are of polymeric material.
9. The process of Claim 8 wherein said polymeric material is coated with a thin layer of metal.
10. A cavity sealing bag for blocking a passageway, stiffening adjacent body panels and restricting noise, vibration and harshness comprising at least a pair of similar panels (11) joined and sealed at their edges, one of said panels having a valve (12) positioned adjacent to an edge to permit inflation of the bag and sealing of the inflated bag.
11. A cavity bag according to Claim 10 wherein said bag is formed of a gas impermeable flexible material.
12. A cavity bag according to Claim 11 wherein said gas impermeable flexible material is a polymeric material.
13. A cavity bag according to Claim 12 wherein said polymeric material is selected from the group consisting of polyvinylchloride (PVC), styrene butadiene rubber (SBR), neoprene, polyesters, polyethylene, nylon, natural rubber and mixtures thereof.
14. A cavity bag according to Claim 10 wherein said polymeric material is coated with a metal coating.
15. A cavity bag according to Claim 10 wherein at least one of said panels of said bag is treated to increase the coefficient of friction.
16. A cavity bag according to Claim 10 wherein at least one of said panels of said bag is coated with an adhesive.

17. A cavity bag according to Claim 10 wherein said bag is of diamond shape.
18. A cavity bag according to Claim 10 wherein said bag is of oblong shape.
- 5 19. A vehicle having a cavity said cavity comprising a cavity sealing bag comprising at least a pair of similar panels (11) joined and sealed at their edges, one of said panels having a valve (12) positioned adjacent to an edge to permit inflation of the bag and sealing of the inflated bag.
- 10 20. A vehicle according to Claim 19 wherein said cavity is found in a location selected from a group consisting of a rocker panel, a removable access panel, a column, a door, a roof, an opening behind a sub-assembly rocker panel, a stoppered drain hole and other stoppered holes.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5

NOT TO BE CONSIDERED FOR PCT PROCEDURE

FIGS 6 & 7

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 98/14333

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 B60P7/06 B60R13/08

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 B60P B60R B65D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 269 890 A (R. BREITLING) 26 May 1981	1, 2, 4, 5,
A	see the whole document ---	7, 8 10-20
X	EP 0 317 130 A (D.A. PHARO) 24 May 1989	1, 2, 6-8,
	see the whole document ---	10-13
A	EP 0 439 086 A (H. HEINRICH) 31 July 1991	1-20
	see the whole document ---	
A	US 3 939 995 A (R.O. BAXTER) 24 February 1976	1-20
	see the whole document ---	
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

5 March 1999

Date of mailing of the international search report

12/03/1999

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Kusardy, R

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 98/14333

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>US 4 553 887 A (R.L. REEVES) 19 November 1985 cited in the application see the whole document -----</p>	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 98/14333

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4269890 A	26-05-1981	DE 2747721 A FR 2407116 A GB 2007337 A, B JP 54070365 A	26-04-1979 25-05-1979 16-05-1979 06-06-1979
EP 317130 A	24-05-1989	US 4793123 A AT 74097 T AU 2466088 A CA 1302962 A DE 3869559 A GR 3004967 T JP 1240465 A PH 26172 A	27-12-1988 15-04-1992 18-05-1989 09-06-1992 30-04-1992 28-04-1993 26-09-1989 18-03-1992
EP 439086 A	31-07-1991	US 5042663 A CA 2034840 A DE 59101247 D	27-08-1991 26-07-1991 05-05-1994
US 3939995 A	24-02-1976	AU 8544175 A CA 1040932 A DE 2548374 A JP 51070079 A	07-04-1977 24-10-1978 06-05-1976 17-06-1976
US 4553887 A	19-11-1985	AU 3111684 A CA 1213783 A EP 0133749 A JP 60045170 A	07-02-1985 11-11-1986 06-03-1985 11-03-1985